created via: HPDC Online Builder

HPD UNIQUE IDENTIFIER: 26130

CLASSIFICATION: 08 11 00 Metal Doors and Frames

PRODUCT DESCRIPTION: This HPD covers knockdown steel frames manufactured by Métalec. Steel frames are made of 16 gauge galvannealed steel. Product dimensions are 36" x 84" x 5¾". Métalec steel frames are compliant to ASTM A 653/A 653M, CAN/ULC - S104 - M80, UBC 7-2(1994),

UL10(b), NFPA 252, NFPA 80, CSDMA, NAAMM, HMMA, ASTM E 152.



Section 1: Summary

Nested Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format Nested Materials Method

Basic Method

Threshold Disclosed Per

Material

Product

Threshold level C 100 ppm

⊙ 1,000 ppm C Per GHS SDS

Other

Residuals/Impurities Considered in 3 of 4 Materials

Explanation(s) provided for Residuals/Impurities?

Residuals/Impurities

Yes ○ No

All Substances Above the Threshold Indicated Are:

Characterized

○ Yes Ex/SC ○ Yes ○ No

% weight and role provided for all substances.

Screened ○ Yes Ex/SC
○ Yes
○ No

All substances screened using Priority Hazard Lists with

results disclosed.

Identified ○ Yes Ex/SC ⊙ Yes ○ No

All substances disclosed by Name (Specific or Generic)

and Identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

GALVANNEALED STEEL (STEEL FRAME) [IRON (IRON) LT-P1 | END CHROMIUM (CHROMIUM) LT-P1 | END | SKI | RES NICKEL (NICKEL) LT-1 | CAN | RES | MUL | SKI | MAM MANGANESE (MANGANESE) LT-P1 | END | MUL | REP ZINC (ZINC) LT-P1 | END | MUL | AQU | PHY] GALVANNEALED STEEL (REINFORCEMENTS) [IRON (IRON) LT-P1 | END CHROMIUM (CHROMIUM) LT-P1 | END | SKI | RES NICKEL (NICKEL) LT-1 | CAN | RES | MUL | SKI | MAM MANGANESE (MANGANESE) LT-P1 | END | MUL | REP ZINC (ZINC) LT-P1 | END | MUL | AQU | PHY] GALVANNEALED STEEL (STRIKE REINFORCEMENT) [IRON (IRON) LT-P1 | END CHROMIUM (CHROMIUM) LT-P1 | END | SKI | RES NICKEL (NICKEL) LT-1 | CAN | RES | MUL | SKI | MAM MANGANESE (MANGANESE) LT-P1 | END | MUL | REP ZINC (ZINC) LT-P1 | END | MUL | AQU | PHY] PAINT [TITANIUM DIOXIDE (TITANIUM DIOXIDE) LT-1 | CAN | END BUTOXYPROPANOL

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Special Conditions materials are present in the product: metal alloy material. Guidelines for reporting Metals (SCMetalAlloy/2020-08-06) were followed even though they are not yet in effect. The full metal alloy composition were reported.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

(BUTOXYPROPANOL) LT-UNK | SKI | EYE]

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional

VOC emissions: CDPH Standard Method - Not tested

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients Option 1

Third Party Verified?

O Yes No

PREPARER: Vertima VERIFIER:

VERIFICATION #:

SCREENING DATE: 2021-09-23 PUBLISHED DATE: 2021-09-23 EXPIRY DATE: 2024-09-23

Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

GALVANNEALED STEEL (STEEL FRAME)

%: 93.2100

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

MATERIAL TYPE: Metal

RESIDUALS AND IMPURITIES NOTES: According to the manufacturer, Lead and Cadmium are present in trace amount, generally inferior to 1 ppm in steel products. These impurities are coming from the sourced iron ore. Passivation surface treatment with a chromic acid solution leaves a total chromium residual of 11 to 27 mg/m² per side.

OTHER MATERIAL NOTES: 18 Ga galvannealed carbon steel sheets with a passivation surface treatment.

IRON (IRON) ID: 7439-89-6

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-09-23 12:28:51

%: 88.3000 - 100.0000 GS: LT-P1 RC: Both NANO: No SUBSTANCE ROLE: Structure component

HAZARD TYPE AGENCY AND LIST TITLES WARNINGS

END TEDX - Potential Endocrine Disruptors Potential Endocrine Disruptor

SUBSTANCE NOTES: Iron is the main element for carbon steel. It is also present in the Galvanneal coating at 11% or between 0.14 to 1.2 wt.% in the final galvannealed sheet. Steel may contain 22% pre consumer recycled content and 34% post consumer recycled content. Percent weight interval is used to cover product variability.

CHROMIUM (CHROMIUM) ID: 7440-47-3

| HAZARD SCREENING METHOD: | Pharos Chemical and Materials Library | HAZARD | SCR | REENING DATE: | 2021-09-23 12:28:58 |
|--------------------------|---------------------------------------|---------|-------|-------------------|--------------------------------------|
| %: 0.0000 - 0.6500 | GS: LT-P1 | RC: Non | е | NANO: No | SUBSTANCE ROLE: Alloy element |
| HAZARD TYPE | AGENCY AND LIST TITLES | \ | WARI | NINGS | |
| END | TEDX - Potential Endocrine Disruptors | | Poten | ntial Endocrine I | Disruptor |
| SKI | MAK | 5 | Sensi | tizing Substanc | ee Sh - Danger of skin sensitization |
| RES | AOEC - Asthmagens | , | Asthn | nagen (Rs) - ser | nsitizer-induced |

SUBSTANCE NOTES: Chromium is an alloying element in carbon steel as well as a residual coming from the passivation surface treatment of galvanneal steel sheets. See all material notes for further details. Percent weight interval is used to cover product variability.

NICKEL (NICKEL) ID: 7440-02-0

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-09-23 12:28:58

%: 0.0000 - 0.2500 GS: LT-1 RC: None NANO: No SUBSTANCE ROLE: Alloy element

| HAZARD TYPE | AGENCY AND LIST TITLES | WARNINGS |
|-------------|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| CAN | US CDC - Occupational Carcinogens | Occupational Carcinogen |
| CAN | MAK | Carcinogen Group 1 - Substances that cause cancer in man |
| CAN | IARC | Group 1 - Agent is Carcinogenic to humans |
| CAN | CA EPA - Prop 65 | Carcinogen |
| CAN | US NIH - Report on Carcinogens | Known to be a human Carcinogen |
| CAN | IARC | Group 2b - Possibly carcinogenic to humans |
| RES | AOEC - Asthmagens | Asthmagen (Rs) - sensitizer-induced |
| CAN | US NIH - Report on Carcinogens | Reasonably Anticipated to be Human Carcinogen |
| RES | MAK | Sensitizing Substance Sah - Danger of airway & skin sensitization |
| MUL | German FEA - Substances Hazardous to Waters | Class 2 - Hazard to Waters |
| SKI | EU - GHS (H-Statements) | H317 - May cause an allergic skin reaction [Skin sensitization - Category 1] |
| CAN | EU - GHS (H-Statements) | H351 - Suspected of causing cancer [Carcinogenicity - Category 2] |
| MAM | EU - GHS (H-Statements) | H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1] |
| | | |

SUBSTANCE NOTES: Percent weight interval is used to cover product variability.

| MANGANESE (MANGANESE) | | | | ID: 7439-96 |
|--------------------------|------------------------------------------|----------|---------------------------------------|--------------------------------------------------|
| HAZARD SCREENING METHOD: | Pharos Chemical and Materials Library | HAZARD S | SCREENING DATE | : 2021-09-23 12:28:59 |
| %: 0.0000 - 2.2000 | GS: LT-P1 | RC: None | NANO: No | SUBSTANCE ROLE: Alloy element |
| HAZARD TYPE | AGENCY AND LIST TITLES | W | 'ARNINGS | |
| END | TEDX - Potential Endocrine Disruptors | P | otential Endocrine | Disruptor |
| MUL | German FEA - Substances Hazardous Waters | to C | lass 2 - Hazard to \ | Waters |
| REP | GHS - Japan | | 360 - May damage production - Cate | fertility or the unborn child [Toxic to gory 1B] |

| ZINC (ZINC) | | | | ID: 7440-66-6 |
|--------------------------|---------------------------------------|------------|---------------|-----------------------------|
| HAZARD SCREENING METHOD: | Pharos Chemical and Materials Library | HAZARD SCF | REENING DATE: | 2021-09-23 12:28:59 |
| %: 0.0000 - 8.8000 | GS: LT-P1 | RC: None | NANO: No | SUBSTANCE ROLE: Galvanizing |

| HAZARD TYPE | AGENCY AND LIST TITLES | WARNINGS |
|-------------|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| END | TEDX - Potential Endocrine Disruptors | Potential Endocrine Disruptor |
| MUL | German FEA - Substances Hazardous to Waters | Class 2 - Hazard to Waters |
| AQU | EU - GHS (H-Statements) | H400 - Very toxic to aquatic life [Hazardous to the aquatic environment (acute) - Category 1] |
| AQU | EU - GHS (H-Statements) | H410 - Very toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 1] |
| PHY | EU - GHS (H-Statements) | H250 - Catches fire spontaneously if exposed to air [Pyrophoric liquids; Pyrophoric solids - Category 1] |
| РНҮ | EU - GHS (H-Statements) | H260 - In contact with water releases flammable gases which may ignite spontaneously [Substances and mixtures which, in contact with water, emit flammable gases - Category 1] |

SUBSTANCE NOTES: Galvanneal is composed of 88% zinc and 11% iron according to the manufacturer. Percent weight interval is used to cover product variability.

GALVANNEALED STEEL (REINFORCEMENTS)

%: 6.3100

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

MATERIAL TYPE: Metal

RESIDUALS AND IMPURITIES NOTES: According to the manufacturer, Lead and Cadmium are present in trace amount, generally inferior to 1 ppm in steel products. These impurities are coming from the sourced iron ore. The surface is passivated (dry). Surface treatment is less than 0.5% of the part weight; hence below the declaration threshold.

OTHER MATERIAL NOTES: Lock and hinges reinforcement are made of galvanneal steel.

| IRON (IRON) | | | | ID: 7439-89-6 |
|--------------------------|---------------------------------------|----------|---------------|-------------------------------------|
| HAZARD SCREENING METHOD: | Pharos Chemical and Materials Library | HAZARD S | SCREENING I | DATE: 2021-09-23 12:28:52 |
| %: 87.8000 - 100.0000 | GS: LT-P1 | RC: Both | NANO: No | SUBSTANCE ROLE: Structure component |
| HAZARD TYPE | AGENCY AND LIST TITLES | W | ARNINGS | |
| END | TEDX - Potential Endocrine Disruptors | Po | otential Endo | crine Disruptor |
| | | | | |

SUBSTANCE NOTES: See Other Material Notes. Steel may contain 14-22% pre consumer recycled content and 19-34% post consumer recycled content. Percent weight interval is used to cover product variability.

| ı | CHROMIUM (CHROMIUM) | | | | | | ID: 7440-47-3 |
|---|--------------------------|---------------------------------------|--------|------|--------------------|--------------------------|---------------|
| | HAZARD SCREENING METHOD: | Pharos Chemical and Materials Library | HAZAF | D SC | REENING DATE: | 2021-09-23 12:28:54 | |
| | %: 0.0000 - 0.6000 | GS: LT-P1 | RC: No | ne | NANO: No | SUBSTANCE ROLE: A | lloy element |
| | HAZARD TYPE | AGENCY AND LIST TITLES | | WAI | RNINGS | | |
| | END | TEDX - Potential Endocrine Disruptors | | Pote | ential Endocrine [| Disruptor | |
| | SKI | MAK | | Sen | sitizing Substanc | e Sh - Danger of skin se | ensitization |
| | RES | AOEC - Asthmagens | | Asth | nmagen (Rs) - ser | nsitizer-induced | |
| | | | | | | | |

NICKEL (NICKEL) ID: 7440-02-0

| HAZARD SCREENING METHOD: | Pharos Chemical and Materials Library | HAZARD SCREENING DATE: 2021-09-23 12:28:57 |
|--------------------------|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| %: 0.0000 - 0.2000 | GS: LT-1 | RC: None NANO: No SUBSTANCE ROLE: Alloy element |
| HAZARD TYPE | AGENCY AND LIST TITLES | WARNINGS |
| CAN | US CDC - Occupational Carcinogens | Occupational Carcinogen |
| CAN | MAK | Carcinogen Group 1 - Substances that cause cancer in man |
| CAN | IARC | Group 1 - Agent is Carcinogenic to humans |
| CAN | CA EPA - Prop 65 | Carcinogen |
| CAN | US NIH - Report on Carcinogens | Known to be a human Carcinogen |
| CAN | IARC | Group 2b - Possibly carcinogenic to humans |
| RES | AOEC - Asthmagens | Asthmagen (Rs) - sensitizer-induced |
| CAN | US NIH - Report on Carcinogens | Reasonably Anticipated to be Human Carcinogen |
| RES | MAK | Sensitizing Substance Sah - Danger of airway & skin sensitization |
| MUL | German FEA - Substances Hazardous Waters | to Class 2 - Hazard to Waters |
| SKI | EU - GHS (H-Statements) | H317 - May cause an allergic skin reaction [Skin sensitization - Category 1] |
| CAN | EU - GHS (H-Statements) | H351 - Suspected of causing cancer [Carcinogenicity - Category 2] |
| MAM | EU - GHS (H-Statements) | H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1] |

SUBSTANCE NOTES: Percent weight interval is used to cover product variability.

| MANGANESE (MANGANESE) | | | | | | ID: 7439-96-5 |
|--------------------------|------------------------------------------|--------|------|------------------------------------|---------------------------------------|---------------|
| HAZARD SCREENING METHOD: | Pharos Chemical and Materials Library | HAZAF | D SC | REENING DATE: | 2021-09-23 12:28:57 | |
| %: 0.0000 - 2.1000 | GS: LT-P1 | RC: No | ne | NANO: No | SUBSTANCE ROLE: A | loy element |
| HAZARD TYPE | AGENCY AND LIST TITLES | | WAF | RNINGS | | |
| END | TEDX - Potential Endocrine Disruptors | | Pote | ential Endocrine I | Disruptor | |
| MUL | German FEA - Substances Hazardous Waters | to | Clas | s 2 - Hazard to V | Vaters | |
| REP | GHS - Japan | | | 0 - May damage oduction - Categ | fertility or the unborn ch ory 1B] | ild [Toxic to |
| | | | | | | |

SUBSTANCE NOTES: Percent weight interval is used to cover product variability.

| ZINC (ZINC) | | | | | | ID: 7440-66-6 |
|--------------------------|------------------------------------------|--------|-------|------------------------------------|----------------------------------------------------|----------------------|
| HAZARD SCREENING METHOD: | Pharos Chemical and Materials Library | HAZAR | D SCF | REENING DATE: | 2021-09-23 12:28:58 | } |
| %: 0.0000 - 8.8000 | GS: LT-P1 | RC: No | ne | NANO: No | SUBSTANCE ROLE: | Galvanizing |
| HAZARD TYPE | AGENCY AND LIST TITLES | | WAR | NINGS | | |
| END | TEDX - Potential Endocrine Disruptors | i | Poter | ntial Endocrine D | Disruptor | |
| MUL | German FEA - Substances Hazardous Waters | to | Class | s 2 - Hazard to W | /aters | |
| AQU | EU - GHS (H-Statements) | | | - Very toxic to a onment (acute) - | equatic life [Hazardous Category 1] | s to the aquatic |
| AQU | EU - GHS (H-Statements) | | [Haza | - | equatic life with long la uatic environment (ch | - |
| PHY | EU - GHS (H-Statements) | | | | pontaneously if expos yrophoric solids - Cat | |
| PHY | EU - GHS (H-Statements) | | H260 | - In contact with | n water releases flamr | nable gases |

SUBSTANCE NOTES: See Other Material Notes. According to the manufacturer, zinc coating weight can be up to 10w% of total steel weight. Since we do not have specific data, we are using the full range of 0% to 10%. Percent weight interval is used to cover product variability.

GALVANNEALED STEEL (STRIKE REINFORCEMENT)

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

gases - Category 1]

MATERIAL TYPE: Metal

which may ignite spontaneously [Substances and mixtures which, in contact with water, emit flammable

RESIDUALS AND IMPURITIES NOTES: According to the manufacturer, Lead and Cadmium are present in trace amount, generally inferior to 1 ppm in steel products. These impurities are coming from the sourced iron ore.

%: 0.4800

OTHER MATERIAL NOTES: Strike reinforcement is also made of galvannealed steel. The galvanneal coating was estimated at 10w% max of total steel sheet weight.

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-09-23 12:28:51

%: 88.3000 - 100.0000 GS: LT-P1 RC: Both NANO: No SUBSTANCE ROLE: Structure component

HAZARD TYPE AGENCY AND LIST TITLES WARNINGS

END TEDX - Potential Endocrine Disruptors Potential Endocrine Disruptor

SUBSTANCE NOTES: Iron is the main element for carbon steel. It is also present in the Galvanneal coating. Steel may contain 22% pre consumer recycled content and 34% post consumer recycled content. Percent weight interval is used to cover product variability.

CHROMIUM (CHROMIUM)

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-09-23 12:28:54

%: 0.0000 - 0.6500 GS: LT-P1 RC: None NANO: No SUBSTANCE ROLE: Alloy element

| HAZARD TYPE AG | GENCY AND LIST TITLES | WARNINGS |
|----------------|--------------------------------------|---------------------------------------------------------|
| END TE | EDX - Potential Endocrine Disruptors | Potential Endocrine Disruptor |
| SKI MA | AK | Sensitizing Substance Sh - Danger of skin sensitization |
| RES AO | OEC - Asthmagens | Asthmagen (Rs) - sensitizer-induced |

SUBSTANCE NOTES: Chromium is an alloying element in carbon steel as well as a residual coming from the passivation surface treatment of galvanneal steel sheets. See all material notes for further details. Percent weight interval is used to cover product variability.

| IICKEL (NICKEL) | | | | | ID: 7440 |
|---------------------------|------------------------------------------|---------|-------------------------------------------------------------------|------------|---------------------------------------------------------------------------------|
| HAZARD SCREENING METHOD: | Pharos Chemical and Materials Library | HAZARD | SCREENI | NG DATE | : 2021-09-23 12:28:55 |
| %: 0.0000 - 0.2500 | GS: LT-1 | RC: Non | e NAN | O: No | SUBSTANCE ROLE: Alloy eleme |
| HAZARD TYPE | AGENCY AND LIST TITLES | | WARNINGS | 3 | |
| CAN | US CDC - Occupational Carcinogens | | Occupation | nal Carcin | ogen |
| CAN | MAK | | Carcinogen man | n Group 1 | - Substances that cause cancer i |
| CAN | IARC | | Group 1 - A | Agent is C | arcinogenic to humans |
| CAN | CA EPA - Prop 65 | | Carcinogen | | |
| CAN | US NIH - Report on Carcinogens | | Known to be a human Carcinogen | | |
| CAN | IARC | | Group 2b - Possibly carcinogenic to humans | | |
| RES | AOEC - Asthmagens | | Asthmagen (Rs) - sensitizer-induced | | |
| CAN | US NIH - Report on Carcinogens | | Reasonably Anticipated to be Human Carcinogen | | |
| RES | MAK | | Sensitizing Substance Sah - Danger of airway & skin sensitization | | |
| MUL | German FEA - Substances Hazardous Waters | to | Class 2 - Ha | azard to \ | Waters |
| SKI | EU - GHS (H-Statements) | | H317 - May sensitizatio | | n allergic skin reaction [Skin gory 1] |
| CAN | EU - GHS (H-Statements) | | H351 - Sus Category 2 | | f causing cancer [Carcinogenicity |
| MAM | EU - GHS (H-Statements) | | repeated ex | xposure [| age to organs through prolonged of Specific target organ toxicity - Category 1] |

SUBSTANCE NOTES: Percent weight interval is used to cover product variability.

| MANGANESE (MANGANESE) | | | | | ID: 7439-96-5 |
|------------------------------------|------------------------------|------------|---------------|---------------------|---------------|
| HAZARD SCREENING METHOD: Pharos Ch | emical and Materials Library | HAZARD SCF | REENING DATE: | 2021-09-23 12:28:55 | |
| %: 0.0000 - 2.2000 | GS: LT-P1 | RC: None | NANO: No | SUBSTANCE ROLE: Al | loy element |

| HAZARD TYPE | AGENCY AND LIST TITLES | WARNINGS |
|-------------|---------------------------------------------|---------------------------------------------------------------------------------------|
| END | TEDX - Potential Endocrine Disruptors | Potential Endocrine Disruptor |
| MUL | German FEA - Substances Hazardous to Waters | Class 2 - Hazard to Waters |
| REP | GHS - Japan | H360 - May damage fertility or the unborn child [Toxic to reproduction - Category 1B] |

ZINC (ZINC) ID: 7440-66-6 HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-09-23 12:28:56 GS: LT-P1 SUBSTANCE ROLE: Galvanizing %: 0.0000 - 8.8000 RC: None NANO: No **HAZARD TYPE** AGENCY AND LIST TITLES **WARNINGS END TEDX - Potential Endocrine Disruptors** Potential Endocrine Disruptor Class 2 - Hazard to Waters MUL German FEA - Substances Hazardous to Waters AQU EU - GHS (H-Statements) H400 - Very toxic to aquatic life [Hazardous to the aquatic environment (acute) - Category 1] AQU EU - GHS (H-Statements) H410 - Very toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) -Category 1] PHY H250 - Catches fire spontaneously if exposed to air EU - GHS (H-Statements) [Pyrophoric liquids; Pyrophoric solids - Category 1] PHY EU - GHS (H-Statements) H260 - In contact with water releases flammable gases which may ignite spontaneously [Substances and

SUBSTANCE NOTES: Galvanneal is composed of 88% zinc and 11% iron according to the manufacturer. Percent weight interval is used to cover product variability.

| PAINT | %: 0.0000 - 0.1000 |
|-------|--------------------|
| | |

PRODUCT THRESHOLD: 1000 ppm RESIDUALS AND IMPURITIES CONSIDERED: No

SUBSTANCE NOTES: Percent weight interval is used to cover product variability.

MATERIAL TYPE: Polymeric Material

mixtures which, in contact with water, emit flammable

gases - Category 1]

RESIDUALS AND IMPURITIES NOTES: Residuals or impurities not identified by manufacturer.

OTHER MATERIAL NOTES: Water-based acrylic paint for metal products. Only ingredients presented in the SDS are disclosed in the HPD given that the amount of paint is below the disclosure threshold (1,000 ppm).

| HAZARD SCREENING METHOD: | THOD: Pharos Chemical and Materials Library | | HAZARD SCREENING DATE: | | 2021-09-23 12:28:53 | |
|-----------------------------|------------------------------------------------------|--------|----------------------------------------------------------------------------------|----------|-------------------------|--|
| %: 1.0000 - 10.0000 | GS: LT-1 | RC: No | one | NANO: No | SUBSTANCE ROLE: Pigment | |
| HAZARD TYPE | AGENCY AND LIST TITLES | | WARNINGS | | | |
| CAN | US CDC - Occupational Carcinogens | | Occupational Carcinogen | | | |
| CAN | CA EPA - Prop 65 Carcino route | | ogen - specific to chemical form or exposure | | | |
| CAN | IARC | | Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources | | | |
| CAN | MAK Carcinogen Group 3A - but not sufficient to esta | | Evidence of carcinogenic effects tablish MAK/BAT value | | | |
| END | TEDX - Potential Endocrine Disruptors | | Potential Endocrine Disruptor | | | |
| CAN | MAK | | Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels | | | |
| CAN EU - GHS (H-Statements) | | | H351 - Suspected of causing cancer [Carcinogenicity - Category 2] | | | |

SUBSTANCE NOTES: Percent weight interval is used to cover product variability and keep exact material composition confidential.

BUTOXYPROPANOL (BUTOXYPROPANOL)

ID: 5131-66-8

| HAZARD SCREENING METHOD: Pharos Chemical and Materials Library | | HAZARD SCREENING DATE: | | 2021-09-23 12:28:54 | |
|----------------------------------------------------------------|-------------------------|------------------------------------------------------------------------|----------|------------------------------------------------------------|--|
| %: 1.0000 - 5.0000 | GS: LT-UNK | RC: None | NANO: No | SUBSTANCE ROLE: Solvent | |
| HAZARD TYPE | AGENCY AND LIST TITLES | WARN | WARNINGS | | |
| SKI | EU - GHS (H-Statements) | H315 - Causes skin irritation [Skin corrosion/irritation - Category 2] | | | |
| EYE | EU - GHS (H-Statements) | | | erious eye irritation [Serious eye ation - Category 2A] | |

SUBSTANCE NOTES: Percent weight interval is used to cover product variability and keep exact material composition confidential.



Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

CDPH Standard Method - Not tested

CERTIFYING PARTY: Self-declared APPLICABLE FACILITIES: -

ISSUE DATE: 2021-09- EXPIRY DATE:

21

CERTIFIER OR LAB: -

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES:



Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.



Section 5: General Notes

This HPD does not cover steel frames with thermal breakage.

MANUFACTURER INFORMATION

MANUFACTURER: MÉTALEC ADDRESS: 2150, rue Léon-Hamel Quebec City Quebec G1N 4L2, Canada

WEBSITE: www.metalec.com

CONTACT NAME: Claude Harton

TITLE: General Manager PHONE: 1-877-683-2431 EMAIL: charton@metalec.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity

END Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

LAN Land toxicity

MAM Mammalian/systemic/organ toxicity

MUL Multiple

NEU Neurotoxicity

NF Not found on Priority Hazard Lists

OZO Ozone depletion

PBT Persistent, bioaccumulative, and toxic

PHY Physical hazard (flammable or reactive)

REP Reproductive

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

UNK Unknown

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (due to insufficient data)

LT-P1 List Translator Possible 1 (Possible Benchmark-1)

LT-1 List Translator 1 (Likely Benchmark-1)

LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the

Recycled Types

PreC Pre-consumer recycled content

PostC Post-consumer recycled content

UNK Inclusion of recycled content is unknown

None Does not include recycled content

information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)

NoGS No GreenScreen.

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.